



Product Specification Report

1.1/92300001/1116

Special, ready to use gel, formulated to remove oxidation and black welding marks from stainless steel surfaces.

KRONNIX GEL FAST

Stainless Steel Pickling Gel

FEATURES:

| | |
|-------------------------|---|
| Fast acting | Removes oxidation and black welding marks. |
| Specific | Recommended for satin stainless steel. |
| Excellent finish | Leaves a clean and professional looking finished welded area. |
| Easy to use | Adheres perfectly even on vertical surfaces. |

APPLICATIONS:

The product can be use with all stainless steel surfaces and is especially recommended for satin stainless steel.

SPECIFICATIONS:

Form..... Gel
 Colour..... Translucent
 Odour..... Pungent
 pH (sol 1%)..... <1
 Solubility/Miscibility in water Miscible
 Average yield 300-450 g/m²

INSTRUCTIONS FOR USE:

Shake the product with a plastic or stainless steel utensil (not iron). Apply with an acid-proof brush directly on the welding line. Allow to act for 10 to 30 minutes. Wait for the product to react. During the reaction KRONNIX GEL FAST turns green. Remove any residues with a cloth or sponge and rinse thoroughly with water.

Average yield: Approximately 300-450 gr/m².

ACTIVE INGREDIENTS:

- Mineral acids
- Ammonium bifluoride

PRECAUTIONS FOR USE:

Excessive contact time increases the risk of leaving streaks on treated surfaces. It is advisable to make preliminary tests to optimize the contact time. The contact time should decrease at warmer temperatures. Avoid using on overheated or incandescent surfaces. KRONNIX GEL FAST is a strong acid, hence it can oxidize materials. Handle with the utmost attention. Please refer to the product's MSDS for further information.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.



Zep UK Ltd.
 T • 0151 422 1000
 F • 0151 422 1011
 info@zep.co.uk
 www.zep.co.uk



Zep Italia s.r.l.
 T • 800 016 918
 Numero Verde Tecnico
 800-579185
 tecnico@zepeurope.com
 www.zep.it



Zep Industries BV
 T • 02 347 01 17
 F • 02 347 13 95
 sales@zep.be
 www.zepindustries.be



Zep Industries BV
 T • 0164 250100
 F • 0164 266710
 info@zepbenelux.com
 www.zepindustries.nl



Zep Industries BV
 T • 0521 174158
 F • 0521 5217114
 sales@zepbenelux.com
 www.zepindustries.de