



Product Specification Report

Rev. 1.0

ZEP OFF NEW is an aerosol designed for the removal of adhesives and seals from hard surfaces such as plaster, concrete, brick, unpainted metal, glass, wood etc.

ZEP OFF NEW

Eliminates various types of seals and adhesives from hard surfaces

FEATURES:

Penetrating	Due to its high viscosity, it can fully penetrate and break down the layers on a surface. These layers can then be removed with pressurised water or a brush.
Gel formula	Its gel formula makes it suitable for use on vertical surfaces.
For many surfaces	Allows for the removal of traces of vandalism on hard surfaces such as plaster, concrete, brick, unpainted metal, glass, wood, etc.
Fast acting	Fast results. It is rinsed off with pressurised water, which improves its performance.

APPLICATIONS:

Can be used to remove seals and adhesives of different types, from a variety of surfaces.

SPECIFICATIONS:

Form	Aerosol
Colour	Colourless
Odour.....	Typical
VOC.....	91,3%
Solubilità in acqua.....	Insoluble
Gross volume.....	800 ml
Net volume	600 ml

PRECAUTIONS FOR USE:

Warning: dissolves most common paints like enamel, acrylic paints, epoxy, vinyl, polyurethane and oil based paints.

For further information please refer to the Safety Data Sheet.

ACTIVE INGREDIENTS:

- ✓ Chlorinated solvents
- ✓ Penetrating agents
- ✓ Vapour retardants
- ✓ Emulsifiers
- ✓ Thickeners

INSTRUCTIONS:

Shake well before use.

- Removing adhesives: Hold the can upright at a distance of 15-20 cm from the surface to be treated. Apply the product and leave it to act until the glue forms bubbles and begins to disintegrate. Reapply as needed. Rinse with water (at high pressure if possible) or a solvent.
- Removing seals: Apply as above. Wait 15 to 30 minutes depending on the thickness of the seal. Reapply as needed. Rinse with water (at high pressure if possible) or a solvent.

COMPATIBILITY:

Compatible with iron, steel, bronze, glass, aluminium, wood, concrete, bricks and plaster.

All information in this document is based on our practical experience and/or laboratory tests. Due to the multiplicity of conditions for usage and variable human factors, we recommend that you always test our products for suitability prior to use. At any time, this version of the product specification report may have been revised based on legislation, availability of the individual ingredients or newly acquired information. The current approved version is available upon request.

IT
Zep Italia s.r.l.
 T • 800 016 918
 Numero Verde Tecnico
 800-579185
 tecnico@zep.europa.com
 www.zep.it

UK
Zep UK Ltd.
 T • 0151 422 1000
 F • 0151 422 1011
 info@zep.co.uk
 www.zep.co.uk

BE
Zep Industries BV
 T • 02 347 01 17
 F • 02 347 13 95
 sales@zep.be
 www.zepindustries.be

NL
Zep Industries BV
 T • 0164 250100
 F • 0164 266710
 info@zepbenelux.com
 www.zepindustries.nl

DE
Zep Industries BV
 T • 0521 174158
 F • 0521 5217114
 sales@zepbenelux.com
 www.zepindustries.de